

|          |                     | <b>↓</b>        |   |   |  |  |  |
|----------|---------------------|-----------------|---|---|--|--|--|
| ITEM NO. | MANUFACTURER        | MFG PART #      | DESCRIPTION   |   |  |  |  |
| 1        | Allied Wire & Cable | VPN00472        | Allied part#: AWC PJ-234/9C, Specification: 2/14 AWG, 3/20 AWG, 7/26 AWG, PVC jackets, overall mylar foil shield, OD nom 0.330", 6ft length |   |  |  |  |
| 2        | Amphenol FCI        | 8655MH1501BLF   | Small DSUB shell  | 1 |  |  |  |
| 3        | Amphenol FCI        | 8655MH2501BLF   | Large DSUB shell  | 1 |  |  |  |
| 4        | Conec               | 3007W2SCM99A10X | Combination D-SUB, 7W2, Socket, Solder Cup, Through hole  | 1 |  |  |  |
| 5        | Conec               | 3017W2SCM99A10X | Combination D-SUB, 17W2, Socket, Solder Cup, Through Hole   | 1 |  |  |  |
| 6        | Conec               | 132C10029X      | Combination D-SUB, Socket, Solder Cup   | 4 |  |  |  |
| 1        |                     |                 | 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2   |   |  |  |  |





SCALE: 3:2 SOLDER SIDE VIEW

| PIN# | SIGNAL                      | AWG     | COLOR          |
|------|-----------------------------|---------|----------------|
| 1    | V_Bootstrap                 | 26      | Gray           |
| 2    | Remote Enable               | 26      | Purple         |
| 3    | +15V / +15V_Sense           | 20 / 26 | Green / Blue   |
| 4    | GND (+/-15V return)         | 20      | Red            |
| 5    | -15V / -15V_Sense           | 20 / 26 | Black / Orange |
| A1   | 5V / 5V_Sense               | 14 / 26 | Black / Red    |
| A2   | 5V_Return / 5V_Return_Sense | 14 / 26 | White / Yellow |

|   |  |          |                               |      |                       |         |                 | -        |
|---|--|----------|-------------------------------|------|-----------------------|---------|-----------------|----------|
|   | DRAWN  | Jason P. | 10/23/2017                    |      |                       | PSC     | er              | 1t       |
|   | UNLESS OTHERWISE SPECIFIED:                                    |          | (                             |      | РНО                   | TON     | CS              |          |
|   | DIMENSIONS ARE IN INCHES TOLERANCES: ONE PLACE DECIMAL: ±0.25" |          | TITLE:                        |      |                       |         |                 |          |
|   |  |          | Power Cord for High Power ICE |      |                       |         |                 |          |
| PROPRIETARY AND CONFIDENTIAL  THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF | MATERIAL N/A   |          | SIZE                          | DWG. | . NO.<br><b>PNO04</b> | 71      | REV<br><b>1</b> |          |
| VESCENT PHOTONICS INC. ANY REPRODUCTION IN PART OR AS A WHOLE                                   | FINISH   | N/A      |                               | В    | V                     | PINUU4  | / 4             |          |
| WITHOUT THE WRITTEN PERMISSION OF VESCENT PHOTONICS INC. IS PROHIBITED.                         |  |          | WING                          | SCAL | _E: 1:1               | WEIGHT: | SHEE            | T 1 OF 1 |

## **CABLE MANUFACTURER NOTES**

PIN#

SIGNAL

+15V

-15V

GND (5V Return)

Remote Enable

+15V\_Sense GND (+/-15V Return)

V\_Bootstrap

-15V\_Sense

5V Return Sense

5V\_Sense

- 1) ALL PIN #S ARE DERIVED DIRECTLY FROM MANUFACTURER DATA-SHEETS AND ARE NOT BEING REDEFINED BY THE VISUAL MODELS IN THIS DRAWING
- 2) ITEM NO. 1 IS A CUSTOM MADE CABLE WITH (3) DIFFERENT WIRE GUAGES
- 3) ITEM NO. 6 IS USED ON BOTH D-SUB CONNECTORS, TWICE EACH FOR A TOTAL OF (4)

7

AWG

COLOR Black

White

Gray

Purple

Green

Orange

Black

Yellow

Red

Blue Red

5

4

3

2

DATE

1